




MR-2B



Rating: 6A 125V AC (UL CUL)
 3A 250V AC (UL CUL VDE CB)
 Contact Resistance: 50m Ω Max
 Insulation Resistance: DC 500V 100M Ω Min
 Dielectric Strength: AC1500V 1 minute
 Electrical life: 10,000 cycles
 Operating Temperature: 0°C~85°C


CUT-OUT



mm	X	Y
0.75~1.25	13.6±0.1	9.2±0.1
1.25~2.00	13.7±0.1	9.2±0.1
2.00~3.00	13.8±0.1	9.2±0.1

MATERIAL:

Body: Nylon66, UL rated: 94V-2 min
 Actuator: Nylon66, UL rated: 94V-2 min
 Terminal: Brass, silver or tin plated



X	0	1	3	4	5
Marking	None	•	≡	—	⊥

修正 REVISION	说明 DESCRIPTION	核准 APPROVAL BY	公差 TOLERANCES		角度 ANGLE 1°		单位 DIMENSION UNIT		mm.			
			绘图 DRAWN BY	李双	设计 DESIGNED BY	李双	比例尺 SCALE	1:1	品名 TITLE	图号 DRAWING NO	材质 MATERIAL	处理 FINISH
			核对 CHECKED BY	李新超	核准 APPROVED BY	李新超	日期 DATE	2006 08 17	MR-2B-110-CXN-BB			