

Specifications:

1.Rating:10A 125VAC/6A 250VAC(UL CSA)


6A 250VAC T85 μ (VDE)

2.Contact Resistance:20m Ω (max.)

3.Insulation Resistance:DC 500V 100M Ω (min.)


4.Dielectric Strength:1500VAC/1 Minute

5.Safety Approval:  E246644



N.W.:3g

MR-1-110-C5N-BR




N.W.:3.7g

MR-1-114-C5N-BB







N.W.:3.7g

MR-1-130-C6N-WW




N.W.:3.2g

MR-1-110-SCL-BR




W	Panel Thickness
19.2	0.75-1.25
19.4	1.25-2.0
19.8	2.0-3.0



N.W.:1g

A-001(MR-1CAP)



HOW TO ORDER

系列號	基座形狀	功能	端子	柄形狀	印字	帶燈指示	基座顏色	柄顏色
1		11 ON-OFF 2P	0	C	0 無印字	N 不帶燈	A 灰色	A 灰色
2		12 ON-ON 3P	1	F	1	L 帶燈	B 黑色	B 黑色
2A		13 ON-OFF-ON 3P	1	P	2	C 魚眼LED燈	W 白色	G 綠色
3		14 (ON)-OFF 2P	2	R	3	w 視窗燈		R 紅色
4		15 ON-(OFF) 2P	3		4			O 橘色
5		21 ON-OFF 4P	4		5			W 白色
6		22 ON-ON 6P	5		6			
		23 ON-OFF-ON 6P	6					
		24 (ON)-OFF 4P						
		25 ON-(OFF) 4P						
		26 (ON)-ON 6P						

备注:

1.端子4弯向.

2.端子5弯向.